



unit:(+0.5mm)

Features: supply DC Power 9V (DC 5V optional with UCD-110-5V) output for Camera and AV composite input Captures video at resolutions up to 720 x 480 (NTSC) or 720 x 576 (PAL/SECAM) Connects to Windows XP machines USB 2.0 port Integrated input connections with mini 4 pin Video can be directly captured as .AVI, compressed AVI, MPEG-1 or Windows Media Video Capture VIDEO from any SPY Camera to your computer hard drive Burn Video to disc in Video CD format **CD Driver step:** Insert the CD into your PC CD-ROM drive. RUN PC CD-ROM drive: SETUP.EXE Connect the UCD-100 to an available USB 2.0 Port. Follow driver installation steps to complete hardware driver installation. **PC Requirements:** Windows XP (Windows 98 or higher) CPU Speed of 2.0 GHz or faster 256 MB of RAM (512 recommended) 600 MB of hard drive space for software installation 4 GB+ of hard disk for video capture space Available USB 2.0 port Graphic card set to 1024 x 768 Sound Card for audio playback

Power Supply:(Ordering in advance)



UCD-110

Instruction Drawing & Description

CD drive for software installation

DC Power 5V (UCD-110-5V)

DC Power 9V (UCD-110-9V)

DC Power 12V (UCD-110-12V)

