

▶ 17" LCD DISPLAY

X-17AV



▶ FEATURES

- Distinctive and modern design
- Metal housing for additional strength
- NeoV Optical Filter
- High 500 contrast ratio
- 170° wide viewing angle
- DVI ready for high quality signal
- S-Video and CVBS inputs (X-17AV only)
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount



▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	17.0" (431.8mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264mm
	Brightness	250cd/m ² (Typical)
	Contrast Ratio	500:1 (Typical)
	Surface Treatments	Hard coating (3H), anti-glare treatment
	Viewing Angle (H/V)	170°/170° (Typical)
	Wide Viewing Angel	Yes
	Display Color	16.7M
Input	Response Time (R/F)	15ms / 10ms (Typical)
	Frequency (H/V)	H: 30kHz - 80kHz V: 50Hz - 75Hz
Connector	Max. Pixel Clock	135MHz
	Analog	15-Pin D-Sub
	Digital (DVI-D)	29-Pin DVI
	S-Video	4-Pin Mini Din S-Video
NeoV Optical Filter	CVBS	CVBS Jack
	Power	3-Pin AC Plug
	Thickness	3.0mm (0.18")
Tilt	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Mounting	Tilt	0° ~ 15°
Dimensions	VESA FPMPMI	Yes (100mm)
	Net (W x H x D)	408 x 398 x 175 mm (16.1" x 15.6" x 6.9")
Weight	Packing (W x H x D)	495 x 510 x 228 mm (19.5" x 20.0" x 9.0")
	Net Weight	6.8Kg (13.9lbs)
Regulation Approval	Gross Weight	9.5Kg (20.9lbs)
	Safety & EMI	FCC, UL, CUL, EPA, TCO 95, TUV/BAURT, CE, NORDIC, NUTEK, BSMI, VCCI, CCC, CB, ISO 13406
Power	VESA	DDC 1/2B, DPMS
	Power AC Consumption	100 - 240V, 50 - 60Hz <48W (On) <5W (Stand-by) <5W (Off)

* All specifications are subject to change without prior notice.

▶ CONTACT INFORMATION

BLOUDEX ELECTRONIC'S
 25, avenue Parmentier 75011 PARIS
 T: 01.48.05.12.12
 F: 01.48.05.66.32
www.bloudex.com