

▶ 19" LCD DISPLAY

X-19AV



▶ FEATURES

- Distinctive and modern design
- Metal housing for additional strength
- NeoV Optical Filter
- Crisp 700 contrast ratio
- Super wide viewing angle technology
- DVI ready for high quality signal
- S-Video and CVBS inputs (X-19AV only)
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount



▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	19" (482.6mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294mm
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	700:1 (Typical)
	Surface Treatments	Hard Coating (2H), anti-glare treatment
	Viewing Angle (H/V)	170°/170° (Minimum)
	Uni-Directional	160° (Typical)
	Display Color	16.7M
Input	Response Time (R/F)	15ms / 10ms (Typical)
	Frequency (H/V)	H: 30kHz - 80kHz V: 50Hz - 75Hz
Connector	Max. Pixel Clock	135MHz
	Analog	15-Pin D-Sub
	Digital (DVI-D)	29-Pin DVI
	S-Video	4-Pin Mini Din S-Video
NeoV Optical Filter	CVBS	CVBS Jack
	Power	3-Pin AC Plug
	Thickness	3.0mm (0.18")
Tilt	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Mounting	Tilt	0° ~ 15°
Dimensions	VESA FPMPMI	Yes (100mm)
	Net (W x H x D)	444 x 419 x 175 mm (17.5" x 16.5" x 6.9")
Weight	Packing (W x H x D)	540 x 525 x 228 mm (21.2" x 20.7" x 9.0")
	Net Weight	TBD
Regulation Approval	Gross Weight	TBD
	Safety & EMI	FCC, UL, CUL, EPA, TCO 95, TUV/BAURT, CE, NORDIC, NUTEK, BSMI, VCCI, CCC, CB, ISO 13406
Power	VESA	DDC 1/2B, DPMS
	Power AC	100 - 240V, 50 - 60Hz
	Consumption	TBD (On) TBD (Stand-by) TBD (Off)

* All specifications are subject to change without prior notice.

▶ CONTACT INFORMATION

BLOUDEX ELECTRONIC'S
 25, avenue Parmentier 75011 PARIS
 T: 01.48.05.12.12
 F: 01.48.05.66.32
www.bloudex.com